

A

Industrial heater for indoor use



Technical Features

- ▶ Steel shielded heating element.
- ▶ All models with contactors.
- ▶ Ambient thermostat with probe.
- ▶ Time delay thermostat.
- ▶ Safety thermostat.
- ▶ Switch for air only (green light).
- ▶ Heat switch (red light).
- ▶ Support bracket to position in any location.
- ▶ Epoxy powder coating RAL 9010 steel structure.
- ▶ Class I insulation.

MODEL		A-4 single phase	A-4 three phase	A-6 three phase	A-9 three phase	A-12 three phase
Input	W	4000	4000	6000	9000	12000
Output	kcal/h	3456	3456	5184	7776	10368
Voltage	V	220-240 V~	3x400 V+N~	3x400 V+N~	3x400 V+N~	3x400 V+N~
Frequency	Hz	50-60	50-60	50-60	50-60	50-60
Air flow	m³/h	400	400	600	750	900
Sound level	dB(A)	49	49	49	54	54
Dimensions	cm	27.2x33.6x24	27.2x33.6x24	34x38.5x25	34x38.5x36	34x38.5x36
Weight	kg	8.7	8.7	10.4	12.8	14
Units per pallet		32	32	32	24	24
EAN 13		8432336600104	8432336600111	8432336600203	8432336600302	8432336600401