

# ADL

## Dynamic Storage Heater / Fan Forced Storage Heater



### Technical features

- ▶ Designed to use Off-Peak electricity.
- ▶ Efficient solution to obtain constant heat when is required during 24 hours a day.
- ▶ Low speed silent fan.
- ▶ Hot air/fresh air mixer with thermostat for a homogenous air output.
- ▶ Precise control over the released heat.
- ▶ Charging thermostat with sensor tube.
- ▶ Safety thermostat with manual reset.
- ▶ Class I insulation.
- ▶ Connection in one or three phases.
- ▶ Microtherm G 25 mm insulation.
- ▶ Vermiculite and ceramic fibre insulations.
- ▶ Front and side air chambers.
- ▶ Powder coated RAL 9010 steel structure.
- ▶ It works together with Ambient Thermostats TA3, TA4D, CTP10 and X2D, available as accessory.

MODEL		ADL-2012	ADL-3018	ADL-4024	ADL-5030
Output 230 V / 240 V	W	2000 / 2178	3000 / 3267	4000 / 4355	5000 / 5444
Accumulated energy	kWh	16	24	32	40
Length	cm	63	81	99	117
Width*	cm	24	24	24	24
Height	cm	66	66	66	66
Total weight	kg	117	167	215	265
Number of Blocks 7.1kg		12	18	24	30
Frequency	Hz	50	50	50	50
Units per pallet		8	8	8	8
EAN 13		8432336200458	8432336200465	8432336200472	8432336200489

\*Plus 2cm space from the wall